



WINDOW UNIT

"V" SOCKET W/TOOLED SEALANT
TOOLED SEALANT

TYPAR ALL TEMPERATURE FLASHING

STRUCTALATH TT 2.5 NO FASTENERS HERE
- FOAM ADHESIVE PER WALL PATTERN

3/4" CEMENT CLADDING COATED WITH
12MIL (min) DRYLOK EXTREME

TYPAR HOUSEWRAP

RODDED CORNER - NO
CORNER ACCESSORY
PERMITTED

LATH SCREWS
STRUCTALATH IS TO BE FORMED OUT
OF SINGLE SECTION WITH VERTICAL
AND HORIZONTAL LEGS BENT FORMING
TO THE STRUCTURE. SECURE WITH
SCREWS AS SHOWN. USE SPOT
ADHESIVE ON ANGLED SECTION -
PATTERN AS PER WALL FASTENING
REQUIREMENT

1.5" min
3" min

LAP WIRE 1 NEST MIN

SILL SLOPE 12" min 1/2"

SCS 07-04 SELF-ADHERED FLASHING
LEDGE, POTSHelf OR SHOULDER

Note:
Details to be used in conjunction with all
applicable provisions contained in the
Sealed Cladding System Design Manual.

Sealed Cladding System

07/01/2020

SCS 07_04